

A12 SPECS

Processor Type	Intel Pentium M with 533MHz or 400MHz FSB and 2MB L2 cache (Dothan 90nm), and support for the Celeron M with 1MB L2 cache
Processor Speeds	1.60GHz - 2.13GHz, 533MHz FSB 1.30GHz - 2.10GHz, 400MHz FSB
Chipset	Intel 915GM ("Alviso-GM") / ICH6-M
Memory	2 memory slots expandable to 2 GB using SO-DIMM (200-pin/2.5V) devices. Supports DDR333 or DDR400 SDRAM modules
Graphics	Embedded Intel 915GM internal graphics controller (Intel GMA 900) with up to 128MB shared memory for display cache with Intel® DVMT 3.0 technology (30% faster than 855GME). Supports dual display option and integrated TV out function.
Display	12.1" WXGA (1280x800) Active Matrix TFT "Glare Type" for more vibrant, brighter colors
Hard Drive	2.5" (9.5mm) IDE HDD with support for 40, 60, 80 & 100GB capacities. (5400/4200 RPM drives supported).
Optical Multimedia	Combo (8x DVD-ROM, 24x CD-R, 24x CD-RW & 24x CD-ROM) or a DVD-Dual (2.4X DVD+R DL, 8x DVD-R, 4x DVD-RW, 8x DVD+R, 4x DVD+RW, 8x DVD-ROM, 24x CD-R, 10x CD-RW, 24x CD-ROM)
Networking	Integrated Realtek RTL8101L 10/100 Ethernet
Modem	Integrated AC'97 V.92/56K Fax/modem
PC Card Slot	One PCMCIA 2.1 compliant Type II slot (Ricoh R5C593)

Mouse	Built-in ALPS Touchpad w/ 2 click buttons
Keyboard	86 keys with Windows XP function key, 19mm Pitch / 2.5mm stroke
Sound	Built-in AC'97 Realtek ALC655, SoundBlaster Compatible; Built-in 2 x stereo 2W speakers; Adjust by volume button, K/B hot-key & SW
I/O Ports	1 x RJ-45 LAN Port 1 x RJ-11 Modem Port 1 x DDC2-B compliant VGA 15 pins 1 x 1394a (Firewire) 1 x Microphone-in 1 x Audio-in Kensington Security Lock Hole 3 x USB 2.0 Ports 1 x Audio-out (headphone/SPDIF)
Card Reader	4-in-1 w/MMC, SD, MS, MS Pro flash card support
Wireless	802.11abg
Operating System	Pick from Windows XP PRO or Win XP Home
Additional Software	Cyberlink PowerDVD v5.0 & DVD Solution (Power2Go) for CD/DVD burning
Battery	Lithium-Ion battery w/8 cells and 65 WHr capacity ~4.0 hr. operation time as reported by MobileMark 2002 but dependent upon the OS and software application usage
AC Adapter	Output=> 19V DC, 3.42A, 65W Input => 100~240V AC, 50/60Hz universal
Dimensions	11.92" x 8.85" x 1.10" (WxDxH)
Weight	4.4 lbs (with Battery & ODD); 4.55 lbs fully configured