

A15 SPECS

Processor Type	Intel Pentium M with 533MHz or 400MHz FSB and 2MB L2 cache (Dothan 90nm), and support for the Celeron M with 1MB L2 cache
Processor Speeds	1.60GHz - 2.26GHz, 533MHz FSB 1.30GHz - 2.10GHz, 400MHz FSB
Chipset	Intel 915GM ("Alviso-GM") / ICH6-M
Memory	2 memory slots expandable to 2 GB using SO-DIMM (200-pin/2.5V) devices. Supports DDR333 or DDR400 SDRAM modules
Graphics	Embedded Intel 915GM internal graphics controller (Intel GMA 900) with up to 128MB shared memory for display cache with Intel® DVMT 3.0 technology (30% faster than 855GME). Supports dual display option and integrated TV out function.
Display	15.0" XGA (1024x768) Active Matrix TFT
Hard Drive	2.5" (9.5mm) IDE HDD with support for 40, 60, 80 & 100GB capacities. (5400/4200 RPM drives supported).
Optical Multimedia	Combo (8x DVD-ROM, 24x CD-R, 24x CD-RW & 24x CD-ROM) or a DVD-Dual (2.4X DVD+R DL, 8x DVD-R, 4x DVD-RW, 8x DVD+R, 4x DVD+RW, 8x DVD-ROM, 24x CD-R, 10x CD-RW, 24x CD-ROM)
Networking	NEW! Integrated Realtek RTL8139/810x family 10/100 Fast Ethernet Controller
Modem	Integrated Agere Systems AC'97 V.92/56K Fax/modem
PC Card Slot	One PCMCIA 2.1 compliant Type II slot (Ricoh R5C593)
Mouse	Built-in Elantech Touchpad w/ 2 click buttons

Keyboard	87 keys with Windows XP function key, 19mm Pitch / 2.5mm stroke; 4 launch keys -> web, email, wireless antenna & personal setting
Sound	Built-in AC'97 Realtek ALC655, SoundBlaster Compatible; Built-in 2 x stereo 1W speakers; Adjust volume by K/B hot-keys or in SW
I/O Ports	1 x RJ-45 LAN Port 1 x RJ-11 Modem Port 1 x DDC2-B compliant VGA 15 pins 1 x S-Video composite TV Out 1 x Microphone-in 1 x 1394a (Firewire) Kensington Security Lock Hole 3 x USB 2.0 Ports 1 x Audio-out (headphone/SPDIF)
Card Reader	4-in-1 w/MMC, SD, MS, MS Pro flash card support
Wireless	802.11abg
Express Card	1 built-in ExpressCard slot (PCI Express x1 I/O) supporting the ExpressCard/34 module (34mm x 75mm) and the ExpressCard/54 module (54mm x 75mm).
Operating System	Pick from Windows XP PRO or Win XP Home
Software	Cyberlink PowerDVD v5.0 & DVD Solution (Power2Go) for CD/DVD burning
Battery	Lithium-Ion battery w/9 cells and 7200mAh capacity ~4.0 hr. operation time as reported by MobileMark 2002 but dependent upon the OS and software application usage
AC Adapter	Output=> 19V DC, 3.42A, 65W Input => 100~240V AC, 50/60Hz universal
Dimensions	13" x 10.8" x 1.3" (WxDxH)
Weight	6.4 lbs (with Battery & ODD)