

RA1400 SPECS

Processor	AMD Turion™ 64 MT28 and higher (25W) Mobil AMD Sempron™ 2600+ and higher (25W)
Operating System	Microsoft® Windows® XP - Professional Edition - Home Edition
Chipset	North Bridge: VIA K8N800/A South Bridge: VIA VT8235M-CE
Display	14.1" TFT bright LCD with XGA resolution
Graphics	VIA K8N800 built-in <ul style="list-style-type: none"> AGP 4X/8X hardware 2D/3D video graphic accelerators High performance 128-bit 3D engine 128 double-words hardware command queue System shared memory 16/32/64MB
Memory	One DDR333 SODIMM Slot for 256/512/1024MB (Max. 1GB)
Hard Disk Drive	2.5" 9.5mm high IDE HDD 40/60/80GB with Ultra DMA 100 and S.M.A.R.T. support Anti Shock Mounted HDD (Protection from vibration during transport)
Media Disk Drive	Internal Combo Drive (DVD/CD-RW) or DVD Dual (DVD-R/CD-RW/DVD-RW/DVD+RW)
Audio	Embedded PCI Bus 16-bit audio <ul style="list-style-type: none"> Compliant with AC-97 Hardware Volume Control Two 1W Speakers Built-in Microphone
PCMCIA	PCMCIA 2.1 compliance, support one Type II PC card slot 32-bit PC Card Bus 1.0 architecture
Keyboard	Spill Resistant Keyboard (85 Keys with Windows Key)

Battery	Standard: 6 cells 4400mAh Li-Ion battery (Approx. 3hrs) Optional: 9 cells 6000mAh Li-Ion battery (Approx. 4hrs) *Battery life will vary depending on actual use factors.
Communication	Integrated 56Kbps v.90 Fax/Modem
LAN / Wireless LAN	Ethernet: Integrated 10/100 Mbps Ethernet Wireless: Mini-PCI WLAN module 802.11 b/g
A/C Adapter	Input: AC 100~240V 50/60Hz, Output: 20V/3.0A/60W
Function Key	Fn+F1 (F11): Select Boot device after POST finished Fn+F5: LCD/CRT Display Switch Fn+F2 (F12): Select Boot from LAN function after POST finished Fn+F6: LCD Brightness Decrease Fn+F3: LCD Off/On Toggle Fn+F7: LCD Brightness Increase Fn+F4: Suspend mode
I/O Port	Two USB 2.0 connectors One Mic-In phone jack for external microphone One 9 pin D-sub connector for RS232 serial port One RJ-11 jack for internal 56Kbps V.90 modem One Type II PCMCIA card slot One RJ-45 jack for internal 10/100Mbps Ethernet One 15 pins D-Sub connectors for external monitor One DC-In jack One Line-Out phone jack for external speakers
Dimension	12.3" X 10.11" X 1.3 - 1.39"
Weight	5.94 lbs