

RB1500 SPECS

Processor Type	Intel Pentium-M and upgrade to Dothan CPU when ready
Operating System	Microsoft® Windows® XP - Professional Edition - Home Edition
Chipset	North Bridge: 82855PM South Bridge: 82801DBM (ICH4)
Display	15.1" TFT LCD with SXGA+ resolution (1400 x 1050)
Graphics	ATI Radeon 9700 M11 <ul style="list-style-type: none"> AGP 8x hardware 2D/3D video graphic accelerators A high performance - bit 3D engine™ AGP 2.0 compliant 128MB video memory
Memory	Two DIMM Slots (128/256/512MB/1024MB DDR Module) Max.2GB
System Bios	AMI NoteBIOS <ul style="list-style-type: none"> 512KB (4M bits) flash EEPROM Support shadow RAM BIOS feature Support Boot Block feature Support APM 1.2, DMI 2.0, SMBIOS 2.3, ACPI 2.0, USB2.0, CD-ROM boot, USB-FDD, Boot from LAN
Floppy Disk Drive	Option: External USB 3½" format, 720KB/1.44MB/1.2MB (3 modes)
Hard Disk Drive	2.5" 9.5mm high Hard Disk Drive, 30/40/60/80GB ATA 100 Capacity Hard Disk Drive <ul style="list-style-type: none"> Anti Shock Mounted HDD(Safety of Vibration & Transporting)
Media Disk Drive	Standard: 24x CD-ROM or Option: DVD+CD-RW Combo Drive
Dimension Weight	13.06" (W) X 10.81" (D) X 1.81 (H) Weight = 6.8 lbs

I/O Port	Three USB connectors (USB2.0) One PCMCIA type II card sockets support 32bits Card Bus card One 15 pins D-sub connector for external monitor One Mini-jack for external Speaker One Mini-jack for external Microphone One RJ-11 jack for internal 56Kbps V.90 modem One RJ-45 jack for internal 10/100M bit Ethernet LAN One S-Video port for TV set DC-In jack One IEEE 1394 Port
Audio	Embedded PCI Bus 16-bit Audio <ul style="list-style-type: none"> Sound Blaster Compatible Hardware Volume Control Compliant with AC-97 ver. 2.2 Two 1.5W speaker Built-in Microphone for voice recognition
PCMCIA	PCMCIA 2.1 compliance, support one Type II PC card slot 32-bit PC Card Bus 1.0 architecture
Keyboard	Spill proof keyboard (88-US Keys with windows Key)
Pointing Device	Built-in Touch Pad with two buttons & support Right/Left and roller
Battery	Standard: 9 cell Smart Li-Ion Battery Pack. Battery life: 3 hours and 30min.
Communication	Integrated 56Kbps v.90 Fax/Modem
LAN / Wireless LAN	Integrated 10/100Mbps Ethernet / Internal Mini PCI/ Interface wireless 802.11b/g
A/C Adapter	Input: 100-240V AC50/60Hz, Output: 20V, 4.5A, 90W