

RI1500 SPECS

Processor	<ul style="list-style-type: none">- Intel Dothan 730 (1.6GHz) and higher FSB 533MHz, 2MB L2 Cache- Intel Celeron-M 350 (1.3GHz) and higher FSB 400MHz, 1MB L2 Cache
Dimension Weight	12.99" X 10.83" X 1.57" 6.6 lbs
Chipset	North Bridge: Intel 915GM South Bridge: Intel ICH6-M
Display	15.1" TFT LCD with XGA resolution (1024 x 768) Optional high brightness LCD
Graphics	Integrated in core logic GMA900 <ul style="list-style-type: none">- AGP 16X equivalent hardware 2D/3D video graphic accelerators- A high performance 128-bit 3D engine- 128 double-words hardware command queue- Intel Dynamic Video Memory Technology 3.0- System shared memory up to 128MB
Memory	Two DDR333 SODIMM Slots each for 256/512MB/1024MB (Max 2048MB)
System Bios	AMI Note BIOS <ul style="list-style-type: none">- Including System BIOS, VGA BIOS, PM, PnP- 512KB (4M bits) flash EEPROM- Support shadow RAM BIOS feature- Support Boot Block feature- Support APM 1.2, DMI 2.0, SMBIOS 2.3, ACPI 2.0, USB2.0, CD-ROM boot, USB-FDD, Boot from LAN
Floppy Disk Drive	Option: External USB 3½" format, 720KB/1.44MB/1.2MB (3 modes)
Hard Disk Drive	2.5" 9.5mm high Hard Disk Drive <ul style="list-style-type: none">- Support 40/60/80GB PATA 100 or SATA 150- Anti Shock Mounted HDD(Safety of Vibration & Transporting)
Media Disk Drive	One optical media device choice of: <ul style="list-style-type: none">- 5.25"/12.7mm DVD/CD-RW (COMBO)- 5.25"/12.7mm DVD-R/CD-RW/DVD-RW/DVD+RW (DVD Dual)

Audio	Embedded PCI Bus 16-bit Audio <ul style="list-style-type: none">- Hardware Volume Control- Compliant with AC-97 ver. 2.2<ul style="list-style-type: none">- Two (2) 1W speaker- Built-in Microphone for voice recognition
PCMCIA	PCMCIA 2.1 compliance, support one Type II PC card slot 32-bit PC Card Bus 1.0 architecture
Keyboard	• Spill proof keyboard (88-US Keys with windows Key)
Pointing Device	Built-in Touch Pad with two buttons & support Right/Left and roller
Battery	Standard: 6 cells 2200mAh Li-Ion battery 3S2P 11.1V 48W (3hrs) Optional: 9 cells 2200mAh Li-Ion battery 3S3P 11.1V 73.3W (4.5hrs)
Communication	Integrated 56Kbps v.90 Fax/Modem
LAN / Wireless LAN	Integrated 10/100/1000Mbps Ethernet / Internal Mini PCI/ Interface wireless 802.11b/g
A/C Adapter	Input: 100-240v Auto-sensing, 50-60Hz, Output: 20V 3A, 60W
I/O Port	Three USB connectors(USB2.0) One 15 pins D-sub connector for external monitor One Mini-jack for external Speaker One Mini-jack for external Microphone One RJ-11 jack for internal 56Kbps V.90 modem One RJ-45 jack for internal 10/100/1000M bit Ethernet LAN One S-Video port for TV set One SPDIF Jack One IEEE 1394 Port One 9 pins D-sub connector for RS232 Serial port DC-In jack